

HAUTE PRESSION - R404A



♦ Groupes haute pression plage : 0°C / -15°C

Code	Modèle	Puis. frigo. W ¹⁾			P.abs.W 0°C	Racc. aspi - ref.	Dim. mm Lg - Pf - Ht	Poids kg
		0°C	-5°C	-10°C				
030755500	SC 12 DLXT2 114H5744	1410	1210	1015	807	10-6	473 - 331 - 296	26

MOYENNE ET HAUTE PRESSION - R404A/R507 - R134a



♦ Avec compresseur MTZ
♦ Huile ESTHER 160PZ

GROUPES MGZ

♦ Plage : R404A / R507 : 0°C/-30°C - ambiance 43°C
R134a : +10°C/-15°C - ambiance 38°C



GROUPES HGZ

♦ Groupe bi-ventilateur
♦ Plage : +10°C / -30°C - Température ambiante : maxi +46°C

Code	Modèle ¹⁾	R404A/R507				I maxi A ³⁾	R134a		
		Puis frigo W ²⁾			Pa W 0°C		Puis frigo W ²⁾		Pa W 0°C
		0°C	-10°C	-25°C			0°C	-10°C	
0305800	MGZ016-SOOG	-	1751	776	700	12,6	1940	1160	800
0305810	MGZ022-SOOG	3770	2760	1360	800	15,6	2750	1636	1000
0305815	MGZ028-SOOG	-	3150	1641	1000	16,6	3240	1956	1300
0305840	MGZ050-SOOD	9335	6445	3152	200	13,0	6430	3930	2400
0305451	HGZ018-SOOG	3256	2154	930	1500	12,6	2235	1308	800
0305453	HGZ022-SOOG	4452	3152	1420	1900	16,6	2904	1706	1000
0305455	HGZ022-SOOD	4452	3152	1420	1900	6,7	2904	1706	1000
0305457	HGZ028-SOOG	5094	3887	1855	2400	16,6	3560	2099	1200
0305459	HGZ028-SOOD	5094	3887	1855	2400	7,9	3560	2099	1200
0305461	HGZ032-SOOG	5928	4120	1900	2800	21,7	4102	2437	1500
0305463	HGZ032-SOOD	5928	4120	1900	2800	8,9	4102	2437	1500
0305465	HGZ036-SOOG	7190	4969	2500	3200	21,7	5087	3226	1700
0305467	HGZ036-SOOD	7190	4969	2500	3200	9,9	5087	3226	1700
0305469	HGZ040-SOOD	8424	5883	2630	3700	11,0	5616	3716	1800
0305471	HGZ050-SOOD	11153	7354	3550	4300	13,4	7052	4243	2300
0305473	HGZ064-SOOD	13342	9245	4360	5600	17,5	8629	5196	2900
0305475	HGZ080-SOOD	17055	12290	5700	7200	25,4	11504	7211	3700
0305477	HGZ100-SOOD	20046	13800	6500	8200	24,4	13264	8007	4200
0305479	HGZ125-SOOD	28037	18700	8760	10000	30,0	16711	10233	5000
0305483	HGZ160-SOOD	33456	22690	11690	13500	39,0	22174	14015	6900

1) Alimentation - D : Comp. et Ventilateur 400V/3/50Hz - E : comp. 400V/3/50Hz et ventilateur 230V/1/50Hz G : Comp. et Ventilateur 230V/1/50Hz
2) Puissance à +32°C ambiant - surchauffe 18°K 3) Compresseur + Ventilateurs

DIMENSIONS

Modèle	Raccords asp-liq.	Dim. mm Lg - Pr - Ht
MGZ016-SOOG	1/2 - 3/8	700 - 500 - 392
MGZ022-SOOD	1/2 - 3/8	700 - 500 - 392
MGZ028-SOOG	1/2 - 3/8	700 - 500 - 392
MGZ050-SOOD	7/8 - 1/2	1000 - 700 - 555
HGZ018-SOOG	1/2 - 3/8	700 - 500 - 392
HGZ022-SOOG	1/2 - 3/8	800 - 600 - 442
HGZ022-SOOD	1/2 - 3/8	800 - 600 - 392
HGZ028-SOOG	1/2 - 3/8	800 - 600 - 392
HGZ028-SOOD	1/2 - 3/8	800 - 600 - 442
HGZ032-SOOG/D	5/8 - 1/2	800 - 600 - 442

Modèle	Raccords asp-liq.	Dim. mm Lg - Pr - Ht
HGZ036-SOOG/D	5/8 - 1/2	1000 - 700 - 555
HGZ040-SOOD	5/8 - 1/2	1000 - 700 - 555
HGZ050-SOOD	7/8 - 1/2	1000 - 700 - 555
HGZ064-SOOD	7/8 - 1/2	1200 - 800 - 671
HGZ080-SOOD	1 1/8 - 1/2	1200 - 800 - 671
HGZ100-SOOD	1 1/8 - 5/8	1200 - 800 - 671
HGZ125-SOOD	1 1/8 - 5/8	1500 - 870 - 675
HGZ144-SOOD	1 1/8 - 5/8	1500 - 870 - 975
HGZ160-SOOD	1 1/8 - 5/8	1500 - 870 - 975